

This is to certify that

Pink Batts®

<b>Product description</b>
Fletcher Insulation Pink Batts.
<b>Product purpose or use</b>
Batts can be installed as ceiling, walls or floor insulation in residential or commercial projects.
<b>Certificate holder</b>
<b>Fletcher Insulation</b> 600 Woodstock Ave, Rooty Hill, NSW, 2766 Ph: 1300 654 444 Website: <a href="http://www.insulation.com.au">www.insulation.com.au</a>

**Complies with the National Construction Code 2016:**

- Volume One – J1.2(a), contributes to J1.3 and J1.5 as per the material R-values as listed on Table 1.
- Volume Two – 3.12.1.1(a), contributes to 3.12.1.2, 3.12.1.4, 3.12.1.5 (a) and 3.12.1.6 as per the material R-values as listed on Table 1.

**State Additions or Variations**

- Volume One NSW Section J for Class 2 buildings and Class 4 parts does not apply but is used to support and complement BASIX.
- Volume Two NSW Part 3.12 does not apply but is used to support and complement BASIX.
- Volume One NT Section J: for Class 2 building and Class 4 parts is replaced by BCA 2009 Section J.
- Volume Two NT Part 3.12 is replaced by BCA 2009 Volume Two Part 3.12.
- Volume One QLD Section J: for Class 2 building is replaced by BCA 2009 Section J.



**Subject to the following conditions and limitations:**

1. Product selection, and incorporation into the building design, shall be made by a person who:
  - Has received training in the use, application and technical aspects of the product; and
  - Has ready access to all to the relevant technical information related to the product use.
2. Product installation shall be carried out in accordance with ICANZ Installation Handbook, Installation Guide Part 2, Version 4, October 2016 and the Fletcher Insulation Installation Pink Insulation Batts Guidelines IG6\_Revision\_0\_Issue Date 18/03/2016 by a competent person under the direction of a Builder, both of whom:
  - Have received training in the product installation and been issued a ICANZ Insulation Installer Certificate; and
  - Having issued an Installation Guarantee Certificate.

Product	Nominal Stabilised Thickness (mm)	Material Declared R-Value (m <sup>2</sup> K/W)
R1.5	70	1.5
R2.0	90	2.0
R2.5	130	2.5
R3.0	155	3.0
R3.5	175	3.5
R4.0	195	4.0
R5.0	215	5.0
R6.0	250	6.0

End of the document



<b>CodeMark Certification Body</b>			<u>21/09/2012</u>	<u>1/12/2016</u>	<u>1/12/2019</u>	<u>GM-CM30006</u> <u>Rev C1</u>
Global-Mark Pty Ltd, Suite 4.07, 32 Delhi Road, North Ryde NSW 2113, Australia - <a href="http://www.Global-Mark.com.au">www.Global-Mark.com.au</a>	Herve Michoux Managing Director	Unrestricted Building Certifier, Peter Gardner	Date of issue	Last update	Date of expiry	Certificate Number

This Certificate of Conformity is issued by an accredited certification body under arrangement with JAS-ANZ. The ABCB does not in any way warrant, guarantee or represent that the Product the subject of this Certificate of Conformity conforms with the BCA, nor accepts any liability arising out of the use of the Product. The ABCB disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate. It is advised to check that this Certificate of Conformity is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the ABCB website, [www.abcb.gov.au](http://www.abcb.gov.au)